

MATERIAL SAFETY DATA SHEET

1. Product and Company Identification

Identification of the

preparation

CC669Series

Product use Inkjet printing

Version # 01

Revision date 25-Apr-2012

Company identification Hewlett-Packard Company

3000 Hanover Street Palo Alto, CA 94304-1185

United States

Telephone 650-857-1501

Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209

(Direct) 1-503-494-7199 HP Customer Care Line

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

2. Hazards Identification

Emergency overview Harmful by inhalation and in contact with skin. Irritating to eyes.

Inhalation may result in respiratory irritation.

Acute health effects

Skin contact Avoid contact with skin.

Harmful in contact with skin.

2-Butoxyethyl acetate

Contact with skin may result in irritation. Harmful if absorbed through the skin.

Eye contact Causes eye irritation. Avoid contact with eyes. Contact with eyes may result in irritation and

Irritating to eyes.

2-Butoxyethyl acetate

Contact with eyes may result in irritation.

Gamma Butyrolactone
Irritating to eyes.
Propylene Carbonate

Contact with eyes may result in irritation.

Inhalation Avoid breathing vapors or mists of this product.

Harmful if inhaled.

2-Butoxyethyl acetate

Inhalation may result in respiratory irritation.

Gamma Butyrolactone

Inhalation may result in respiratory irritation.

Ingestion May be harmful if swallowed.

2-Butoxyethyl acetate

Swallowing large amounts may cause digestive discomfort. Harmful if swallowed.

Gamma Butyrolactone

Harmful if swallowed. May depress the central nervous system.

Potential health effects

Routes of exposure Potential routes of exposure under normal use conditions are skin and eye contact; and

inhalation

Material name: CC669Series MSDS US

10477 Version #: 01 Revision date: 25-Apr-2012 Print date: 25-Apr-2012

Carcinogenicity

Carbon black is classified by the IARC as a Group 2B carcinogen (the substance is possibly carcinogenic to humans). Carbon black in this preparation, due to its bound form, does not

present this carcinogenic risk.

None of the other ingredients in this preparation are classified as carcinogens according to ACGIH, EU, IARC, MAK, NTP or OSHA.

Components	CAS #	Percent
2-Butoxyethyl acetate	112-07-2	70 - 80
Carbon black	1333-86-4	2.5 - 5
Gamma Butyrolactone	96-48-0	2.5 - 5
Propylene Carbonate	108-32-7	2.5 - 5
Vinyl chloride-vinyl acetate copolymer	Proprietary	2.5 - 5
High molecular weight block copolymer with pigment affinic groups	No Data	1 - 2.5

Composition comments

Carbon black is present only in a bound form in this preparation.

4. First Aid Measures

First aid procedures

Eye contact Do not rub eyes. In case of contact, immediately flush eyes with large amounts of water,

continuing to flush for 15 minutes. If irritation persists get medical attention.

Skin contact Wash affected areas thoroughly with mild soap and water. Get medical attention if irritation

develops or persists.

Inhalation Move person to fresh air immediately. If symptoms persist, get immediate medical attention.

Ingestion If material is ingested, immediately contact a physician or poison control center.

5. Fire Fighting Measures

Flammable properties

Combustible liquid. Many liquids are lighter than water. Vapors may travel to a source of ignition and flash back. During a fire, irritating and highly toxic gases may be generated by thermal decomposition or combustion.

Extinguishing media

Suitable extinguishing

media

Dry chemical, CO2, water spray or regular foam. Avoid using a direct stream of water.

Unsuitable extinguishing

media

high volume water jet

Specific methods

Do not direct a solid stream of water or foam into hot, burning pools; this may result in frothing and increase fire intensity. Standard procedure for chemical fires. In the event of fire and/or explosion do not breathe fumes. Wear self contained breathing apparatus for fire fighting if

necessary.

Hazardous combustion

products

Refer to section 10.

6. Accidental Release Measures

Personal precautions Avoid contact with skin Remove all sources of ignition. Wear appropriate personal protective

equipment.

Environmental precautions

Other information

Do not let product enter drains. Do not flush into surface water or sanitary sewer system.

Soak up with inert absorbent material. Use personal protective equipment to minimize exposure to skin and eye. Use spark-proof tools and explosion-proof equipment. Dispose of in compliance with

federal, state, and local regulations.

7. Handling and Storage

Handling Use spark-proof tools and explosion-proof equipment. Keep this product from heat, sparks, or

open flame. Avoid contact with skin, eyes and clothing. Keep away from sources of ignition - No

smoking. Use with adequate ventilation.

Storage Keep away from heat, sparks and flame. Keep away from oxidizers. Store at ambient temperature

and atmospheric pressure. Keep away from excessive heat or cold.

Material name: CC669Series MSDS US

8. Exposure Controls / Personal Protection

Occupational exposure limits

ACGIH

Components	Туре	Value	Form
2-Butoxyethyl acetate (112-07-2)	TWA	20.0000 ppm	
Carbon black (1333-86-4)	TWA	3.0000 mg/m3	Inhalable fraction.

U.S. - Tennessee

Components	Туре	Value	
Carbon black (1333-86-4)	TWA	3.5000 mg/m3	

Exposure guidelines Exposure limits have not been established for this product.

Engineering controls Use in a well ventilated area.

Personal protective equipment

General hygiene considerations

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin,

eyes and clothing.

General Use personal protective equipment to minimize exposure to skin and eye.

9. Physical & Chemical Properties

Appearance Not available.

Color Black.

OdorNot available.Odor thresholdNot available.

Physical state Liquid

Form Not available.

pH Not available.

Melting point Not available.

Freezing point Not available.

Boiling point 363.2 °F (184 °C)

Flash point 179.6 °F (82 °C) Cleveland Open Cup

Evaporation rate not determined Flammability limits in air, upper, % by volume onto determined < 1.7 % v/v

apper, 70 by volume

Flammability limits in air,

> 8.4 % v/v

lower, % by volume

Vapor pressure 0.4 hPa **Vapor density** Not available.

Specific gravity 0.97

Relative density

Solubility (water)

Auto-ignition temperature

Decomposition temperature

VOC

Not available.

Not available.

Not available.

88.6 % w/w

10. Chemical Stability & Reactivity Information

Chemical stability Stable under recommended storage conditions.

Incompatible materials Strong oxidizing agents. This product may react with strong acids. This product may react with

strong alkalies.

Hazardous decomposition

products

Oxides of carbon/nitrogen/sulfur, and water. Irritating and/or toxic fumes and gases may be

emitted upon the products decomposition.

Possibility of hazardous

reactions

Will not occur.

Material name: CC669Series MSDS US

11. Toxicological Information

Carcinogenicity

Carbon black is classified as a carcinogen by the IARC (possibly carcinogenic to humans, Group 2B) and by the State of California under Proposition 65. In their evaluations of carbon black, both organizations indicate that exposure to carbon black, per se, does not occur when it remains bound within a product matrix, specifically, rubber, ink, or paint.

ACGIH Carcinogens

2-Butoxyethyl acetate (CAS 112-07-2)

A3 Confirmed animal carcinogen with unknown relevance to

Carbon black (CAS 1333-86-4)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Carbon black (CAS 1333-86-4)

2B Possibly carcinogenic to humans.

Gamma Butyrolactone (CAS 96-48-0) Vinyl chloride-vinyl acetate copolymer (CAS Proprietary)

3 Not classifiable as to carcinogenicity to humans. 3 Not classifiable as to carcinogenicity to humans.

IARC Monographs: Evidence of carcinogenicity in humans

Carbon black (CAS 1333-86-4) Gamma Butyrolactone (CAS 96-48-0)

Inadequate data. Inadequate data.

Vinyl chloride-vinyl acetate copolymer (CAS Proprietary) No data.

Serious eye damage/eye

irritation

Not available.

Symptoms and target organs

Target Organs (NIOSH)

2-Butoxyethyl acetate (CAS 112-07-2)

Blood

Central Nervous System

Eyes

Hemato system Kidneys Liver

Lymphoid system Respiratory system

Skin Eves

Carbon black (CAS 1333-86-4)

Respiratory system

Further information Complete toxicity data are not available for this specific formulation

12. Ecological Information

Aquatic toxicity

This product has not been tested for ecological effects.

Persistence and degradability Not available.

13. Disposal Considerations

Disposal instructions

Dispose of in compliance with federal, state, and local regulations. Do not allow this material to

drain into sewers/water supplies.

14. Transport Information

Further information

Not a dangerous good under DOT, IATA, ADR, IMDG, or RID.

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Not regulated as dangerous goods.

15. Regulatory Information

US federal regulations

US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders under TSCA.

Material name: CC669Series MSDS US 4/6

10477 Version #: 01 Revision date: 25-Apr-2012 Print date: 25-Apr-2012

CERCLA (Superfund) reportable quantity

None

Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical

Yes

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely hazardous substance

No

Section 311 hazardous

Yes

chemical

State regulations

US - Pennsylvania RTK - Hazardous Substances: Listed substance

Carbon black (CAS 1333-86-4) Listed.

Regulatory information Notified according to EU Regulations.

16. Other Information

Other information This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29

CFR 1910.1200).

HMIS® ratings Health: 2

Flammability: 2 Physical hazard: 1

NFPA ratings Health: 2

Flammability: 2 Instability: 1

Disclaimer This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard

Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as guaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and

may not meet regulatory requirements in other countries.

Issue date 25-Apr-2012

This data sheet contains changes from the previous version in section(s):

14. Transport Information: Further information

Manufacturer information Hewlett-Packard Company

3000 Hanover Street

Palo Alto, California 94304-1112 US

(Direct) 1-503-494-7199

(Toll-free within the US) 1-800-457-4209

Material name: CC669Series MSDS U

10477 Version #: 01 Revision date: 25-Apr-2012 Print date: 25-Apr-2012

Explanation of abbreviations

ACGIH American Conference of Governmental Industrial Hygienists

CAS Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

CFR Code of Federal Regulations

COC Cleveland Open Cup

DOT Department of Transportation

EPCRA Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

OSHA Occupational Safety and Health Administration

PEL Permissible Exposure Limit

RCRA Resource Conservation and Recovery Act

REC Recommended

REL Recommended Exposure Limit

SARA Superfund Amendments and Reauthorization Act of 1986

STEL Short-Term Exposure Limit

TCLP Toxicity Characteristics Leaching Procedure

TLV Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds

Material name: CC669Series MSDS US