

## MATERIAL SAFETY DATA SHEET

# 1. Product and Company Identification

Identification of the

preparation

CH148Series

Synonym(s) HP SC101 Yellow Ink

Product use Inkjet printing

Version # 02

Revision date 01-May-2012 CAS # Mixture

**Company identification** Hewlett-Packard Company

3000 Hanover Street Palo Alto, CA 94304-1185

**United States** 

Telephone 650-857-1501

Hewlett-Packard health effects line (Toll-free within the US) 1-800-457-4209

(Direct) 1-503-494-7199 HP Customer Care Line

(Toll-free within the US) 1-800-474-6836

(Direct) 1-208-323-2551

Email: hpcustomer.inquiries@hp.com

#### 2. Hazards Identification

**Emergency overview** Harmful by inhalation and in contact with skin. Contact with skin and eyes may result in irritation.

Inhalation may result in respiratory irritation.

**Acute health effects** 

**Skin contact** Avoid contact with skin.

Harmful in contact with skin.

**Eye contact** Avoid contact with eyes.

Contact with eyes may result in irritation.

**Inhalation** Avoid breathing vapors or mists of this product.

Harmful if inhaled.

**Ingestion** May be harmful if swallowed.

**Potential health effects** 

**Routes of exposure** Potential routes of exposure under normal use conditions are skin and eye contact; and

inhalation

Chronic health effects None known.

**Carcinogenicity**None of the components present in this formulation at concentrations equal to or greater than

0.1% are listed by EU, MAK, IARC, NTP or OSHA.

### 3. Composition / Information on Ingredients

Components	CAS #	Percent
2-Butoxyethyl acetate	112-07-2	>70
2-methoxy-1-methylethylacetate	108-65-6	<10
Cyclohexanone	108-94-1	<10

### 4. First Aid Measures

#### First aid procedures

Eye contact In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under

the eyelids, for at least 15 minutes. Get medical attention immediately.

Material name: CH148Series MSDS US

**Skin contact** In case of contact, immediately remove contaminated clothing and flush skin with copious

amounts of water. Wash clothing separately before reuse.

Get medical attention, if needed.

**Inhalation** Move person to fresh air immediately.

If symptoms persist, get immediate medical attention.

**Ingestion** Rinse mouth out with water. If the material is swallowed, get immediate medical attention or

advice -- Do not induce vomiting. Never give anything by mouth to an unconscious person.

Get medical attention immediately.

# 5. Fire Fighting Measures

#### **Extinguishing media**

Suitable extinguishing media

For small (incipient) fires, use media such as foam, sand, dry chemical, or carbon dioxide.

For large fires use very large (flooding) quantities of water and/or foam, applied as a mist or spray.

## **Protection of firefighters**

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

Avoid runoff into storm sewers and ditches which lead to waterways.

# **Special protective equipment**

for fire-fighters

Firefighters should wear full protective clothing including self contained breathing apparatus.

#### **6. Accidental Release Measures**

**Personal precautions** Avoid contact with skin. Avoid inhalation of vapors or mists.

Do not touch or walk through spilled material. Ensure adequate ventilation. Remove all sources of

ignition.

Use personal protective equipment to minimize exposure to skin and eye. In the case of vapor

formation use a respirator with an approved filter.

**Environmental precautions** 

Do not flush into surface water or sanitary sewer system.

Methods for cleaning up

Absorb with earth, sand or other non-combustible material and transfer to containers for later

disposal.

**Other information** Dispose of in compliance with federal, state, and local regulations.

# 7. Handling and Storage

**Handling** Avoid contact with skin, eyes and clothing. Avoid breathing vapors or mists of this product.

Use with adequate ventilation.
Wear personal protective equipment.

**Storage** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from heat,

sparks and flame.

## 8. Exposure Controls / Personal Protection

#### **Occupational exposure limits**

#### **ACGIH**

Components	Туре	Value	
2-Butoxyethyl acetate (112-07-2)	TWA	20.0000 ppm	
Cyclohexanone (108-94-1)	BEI 8.0000 mg/l	8.0000 mg/l	
		80.0000 mg/l	
	STEL	50.0000 ppm	
	TWA	20.0000 ppm	

# U.S. - OSHA

Components	Туре	Value
Cyclohexanone (108-94-1)	PEL	50.0000 ppm 200.0000 mg/m3

#### **U.S. - Tennessee**

Components	Туре	Value	
Cyclohexanone (108-94-1)	TWA	25.0000 ppm	
		100.0000 mg/m3	

Material name: CH148Series MSDS US

**U.S. - WEEL** 

ComponentsTypeValue2-methoxy-1-methylethylacetate (108-65-6)TWA50.0000 ppm

#### Personal protective equipment

**Eye / face protection** Wear safety glasses; chemical goggles (if splashing is possible).

Eye wash fountain and emergency showers are recommended.

**Skin protection** Wear appropriate chemical resistant clothing.

Wear appropriate chemical resistant gloves.

**Respiratory protection** Provide adequate ventilation. In case of insufficient ventilation wear suitable respiratory

equipment.

General hygiene considerations

Do not get this material in contact with skin. Avoid contact with skin, eyes and clothing. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after

handling the product.

Launder contaminated clothing before reuse.

## 9. Physical & Chemical Properties

Appearance Not available.

Color Yellow.

Odor Solvent.

Odor threshold Not available.

Physical state Liquid

Form Liquid.

pH Not available.
 Melting point Not available.
 Freezing point Not available.
 Boiling point Not available.

Flash point 154.4 °F (68 °C) Closed Cup

Evaporation rate Not available.
Flammability limits in air, Not available.

upper, % by volume Flammability limits in air,

lower, % by volume

Not available.

Vapor pressure Not available. Not available. Vapor density Specific gravity Not available. Not available. Relative density Solubility (water) Not available. **Auto-ignition temperature** Not available. **Decomposition temperature** Not available. VOC 899 g/L

**Other information** For other VOC regulatory data/information see section 15.

## 10. Chemical Stability & Reactivity Information

**Chemical stability**Stable at normal conditions. **Conditions to avoid**Heat, flames and sparks.

Possibility of hazardous

reactions

None known.

## 11. Toxicological Information

#### Carcinogenicity

### **ACGIH Carcinogens**

2-Butoxyethyl acetate (CAS 112-07-2)

A3 Confirmed animal carcinogen with unknown relevance to humans.

Material name: CH148Series

MSDS US

10022 - Marriag #4 02 - Professor date: 01 Marriag 2012 - Print date: 01 Marriag 2012

Cyclohexanone (CAS 108-94-1)

A3 Confirmed animal carcinogen with unknown relevance to

humans

IARC Monographs. Overall Evaluation of Carcinogenicity

Cyclohexanone (CAS 108-94-1) 3 Not classifiable as to carcinogenicity to humans.

IARC Monographs: Evidence of carcinogenicity in humans

Cyclohexanone (CAS 108-94-1) No data.

Serious eye damage/eye

Not available.

irritation

**Sensitization** 

**US ACGIH Threshold Limit Values: Skin designation** 

Cyclohexanone (CAS 108-94-1) Can be absorbed through the skin.

Symptoms and target organs

Target Organs (NIOSH)

2-Butoxyethyl acetate (CAS 112-07-2) Blood

Central Nervous System

Eyes

Hemato system Kidneys Liver

Lymphoid system Respiratory system

Skin

Cyclohexanone (CAS 108-94-1) Central Nervous System

Eyes Kidneys Liver

Respiratory system

Skir

**Further information** Complete toxicity data are not available for this specific formulation

12. Ecological Information

**Ecotoxicity**No information available. **Aquatic toxicity**No information available.

Persistence and degradability Not available.

13. Disposal Considerations

**Disposal instructions** Do not dispose of together with general office waste.

Do not allow this material to drain into sewers/water supplies.

Dispose of waste material according to Local, State, Federal, and Provincial Environmental

Regulations.

Ensure collection and disposal with an appropriately licensed waste contractor.

**14. Transport Information** 

**DOT** 

Basic shipping requirements:

**UN number** NA1993

**Proper shipping name** Combustible liquid n.o.s. (2-methoxy-1-methylethyl acetate, cyclohexanone) -Not regulated in

quantities less than 119 gallons

Hazard class Combustible

Packing group III

Additional information:

ERG number 128

**IATA** 

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

Material name: CH148Series

MSDS US

Not regulated as dangerous goods.

## 15. Regulatory Information

**US federal regulations** 

US EPA TSCA Inventory: All chemical substances in this product comply with all rules or orders

under TSCA.

#### **CERCLA (Superfund) reportable quantity**

#### Occupational Safety and Health Administration (OSHA)

29 CFR 1910.1200 hazardous chemical Yes

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

**Hazard categories** Immediate Hazard - No

Delayed Hazard - Yes Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

Section 302 extremely

hazardous substance

Section 311 hazardous

chemical

Yes

#### State regulations

#### US - Pennsylvania RTK - Hazardous Substances: Listed substance

Cyclohexanone (CAS 108-94-1) Listed.

### **Regulatory information**

Notified according to EU Regulations.

Other information

Specific Provisions: Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC (in the amended version OJ L 396 from 29.05.2007 page 3 with further rectifications

and amendments).

Exposure Limits (See Section 8): Executive regulation of Minister of Labour and Social Policy dated Nov. 29, 2002 concerning the highest exposure limits and volume of factors harmful for health and environment at work (Official Journal of Laws no 217/2002 item 1833 with further amendments). VOC content (less water, less exempt compounds) = < 899 g/L (U.S. requirement, not for

emissions)

### 16. Other Information

Other information

This MSDS was prepared in accordance with USA OSHA Hazard Communications regulation (29

CFR 1910.1200).

**HMIS®** ratings

Health: 2 Flammability: 2 Physical hazard: 1 Personal protection: B

NFPA ratings

Health: 2 Flammability: 2 Instability: 1

**Disclaimer** 

This Safety Data Sheet document is provided without charge to customers of Hewlett-Packard Company. Data is the most current known to Hewlett-Packard Company at the time of preparation of this document and is believed to be accurate. It should not be construed as quaranteeing specific properties of the products as described or suitability for a particular application. This document was prepared to the requirements of the jurisdiction specified in Section 1 above and may not meet regulatory requirements in other countries.

**Issue date** 

01-May-2012

This data sheet contains changes from the previous version in section(s):

This document has undergone significant changes and should be reviewed in its entirety.

Material name: CH148Series 5/6

 Manufacturer information
 Hewlett-Packard Company

3000 Hanover Street

Palo Alto, California 94304-1112 US Product Information 1-800-925-0563

### **Explanation of abbreviations**

**ACGIH** American Conference of Governmental Industrial Hygienists

**CAS** Chemical Abstracts Service

CERCLA Comprehensive Environmental Response Compensation and Liability Act

**CFR** Code of Federal Regulations

**COC** Cleveland Open Cup

**DOT** Department of Transportation

**EPCRA** Emergency Planning and Community Right-to-Know Act (aka SARA)

IARC International Agency for Research on Cancer

NIOSH National Institute for Occupational Safety and Health

NTP National Toxicology Program

**OSHA** Occupational Safety and Health Administration

**PEL** Permissible Exposure Limit

**RCRA** Resource Conservation and Recovery Act

**REC** Recommended

**REL** Recommended Exposure Limit

**SARA** Superfund Amendments and Reauthorization Act of 1986

**STEL** Short-Term Exposure Limit

**TCLP** Toxicity Characteristics Leaching Procedure

**TLV** Threshold Limit Value

TSCA Toxic Substances Control Act
VOC Volatile Organic Compounds

Msds us Msds u